



BEHRMANN BUZZ

February, 2008

Introducing the L.E.S. VI High Efficiency Condensing Boiler

L.E.S., Inc. and Behrmann Company introduce you to the Series VI High Efficiency Condensing Steel Firetube Boiler. Efficiency from 85% to 97%+. These boilers are primarily intended for reduced temperature closed loop hydronic heating applications and are equipped with factory piped and wired high turndown modulating natural gas or LP Power Flame burners.

Standard Features:

- Sealed combustion
- 5 Year warranty
- ASME constructed
- 30-100 psi wp
- CSD-1 compliant burner & controls
- Thermal shock resis-

- tant vertical design
- Single pass vertical firetube
- 40F to 240F operating water temperature
- Fireside condensing surfaces coated

VI Series boilers range in size from 750MBH input to 2000MBH. Standard burner turndown is 5:1.

Call your Behrmann Company sales engineer to assist you with design, application and specification needs.



MACON Valves deliver complete balancing & flow measurement

Behrmann Company would like to acquaint you with an efficient, dependable and cost-effective solution to measuring and balancing system flow rates. MACON balancing valves. Here are some of the Macon balancing valves features:

- "Y" pattern globe style design
- Positive shut-off Offset-

ting pressure/temperature ports, self sealing with optional drain kits

- Ten-turn, 360 degree handwheel with vernier scale and digital readout
- Built-in memory stop
- Sweat, threaded, flanged and grooved connections
- Sizes from 1/2" to 12"



Your Behrmann Company sales engineer is looking forward to working with you on your next HVAC project. Look to us for solutions.